



Environmental product declaration

in accordance with ISO 14025 and EN 15804+A2

Profim Com H



profim

Flol: l:

Owner of the declaration:

Flokk AS

Product:

Profim Com H

Declared unit:

1 pc

This declaration is based on Product Category Rules:

CEN Standard EN 15804:2012+A2:2019 serves as core

NPCR 026:2022 Part B for Furniture

Program operator:

The Norwegian EPD Foundation

Declaration number:

NEPD-6378-5642-EN

Registration number:NEPD-6378-5642-EN

Issue date: 04.04.2024

Valid to: 04.04.2029

EPD software:

LCAno EPD generator ID: 286043

The Norwegian EPD Foundation



General information

Product

Profim Com H

Program operator:

Post Box 5250 Majorstuen, 0303 Oslo, Norway The Norwegian EPD Foundation Phone: +47 23 08 80 00 web: post@epd-norge.no

Declaration number:

NEPD-6378-5642-EN

This declaration is based on Product Category Rules:

CEN Standard EN 15804:2012+A2:2019 serves as core PCR NPCR 026:2022 Part B for Furniture

Statement of liability:

The owner of the declaration shall be liable for the underlying information and evidence. EPD Norway shall not be liable with respect to manufacturer information, life cycle assessment data and evidences.

Declared unit:

1 pcs Profim Com H

Declared unit (cradle to gate) with option:

A1-A3,A4,A5,B2,B3,B4,C1,C2,C3,C4,D

Functional unit:

Profim Com K42H Full Uph shell (Xtreme/Camira), w/o armrests - Including packaging.

General information on verification of EPD from EPD tools:

Independent verification of data, other environmental information and the declaration according to ISO 14025:2010, § 8.1.3 and § 8.1.4. Verification of each EPD is made according to EPD-Norway's guidelines for verification and approval requiring that tools are i) integrated into the company's environmental management system, ii) the procedures for use of the EPD tool are approved by EPD-Norway, and iii) the process is reviewed annually by an independent third party verifier. See Appendix G of EPD-Norway's General Programme Instructions for further information on EPD tools

Verification of EPD tool:

Independent third party verification of the EPD tool, background data and test-EPD in accordance with EPDNorway's procedures and guidelines for verification and approval of EPD tools.

Third party verifier:

Elisabet Amat, GREENIZE projects

(no signature required)

Owner of the declaration:

Contact person: Atle Thiis-Messel Phone: 0047 98 25 68 30 e-mail: atle.messel@flokk.com

Manufacturer:

Flokk AS Drammensveien 145, 0277 Oslo, Norway

Place of production:

Flokk - Turek ul. Górnicza 8 62-700 Turek, Poland

Management system:

ISO 14001, ISO 9001, ISO 50001(Norway, Sweden)

Organisation no:

No 928 902 749

Issue date:

04.04.2024

Valid to:

04.04.2029

Year of study:

2023

Comparability:

EPD of construction products may not be comparable if they not comply with EN 15804 and seen in a building context.

Development and verification of EPD:

The declaration is created using EPD tool lca.tools ver EPD2022.03, developed by LCA.no. The EPD tool is integrated in the company's management system, and has been approved by EPD Norway.

Developer of EPD: Damian Bakowski

Reviewer of company-specific input data and EPD: Monika Kuczynska

Approved:

Håkon Hauan, CEO EPD-Norge



Product

Product description:

Com is a model characterized by lightness, durability and multifunctionality. With the refined geometry of the seat shell, it is also very comfortable. This chair designed by Paul Brooks is perfect for auditoriums, meeting rooms and canteens.

Collection features:

- five types of bases allow any configuration
- the collection is completed with a barstool on a metal wire frame
- the square shape of the shell has four finishing options: plywood, with upholstered seat pad, with seat and backrest pad or fully upholstered
- the shell can come in different finishes: lacquered plywood, lined with natural veneer or HPL laminate which is scratch resistant

Product specification

The model studied in detail in this declaration is the Profim Com K42H fully upholstered in the Xtreme fabric from Camira - including carton box packaging. The key environmental indicators for the other variants/options of the Profim Com H are presented on a table pages 12 of this declaration

Materials	kg	%	Recycled share in material (kg)	Recycled share in material (%)
Adhesive	0,04	0,63	0,00	1,82
Metal - Steel	2,39	37,66	0,45	19,04
Plastic - Polyoxymethylene (POM)	0,01	0,08	0,00	0,00
Plastic - Polypropylene (PP)	0,30	4,70	0,00	0,00
Plastic - Polyurethane (PUR)	0,20	3,19	0,00	0,00
Powder coating	0,03	0,47	0,00	0,00
Printed paper	0,00	0,02	0,00	34,31
Textile - Polyester (PE)	0,73	11,46	0,60	82,26
Wood - Solid beech/birch	2,65	41,79	0,00	0,00
Total	6,34		1,05	

Packaging	kg	%	Recycled share in material (kg)	Recycled share in material (%)
Packaging - Cardboard	0,43	10,38	0,00	0,00
Packaging - Paper	0,02	0,58	0,01	34,31
Packaging - Plastic	0,10	2,45	0,00	0,00
Packaging - Plastic straps	0,01	0,12	0,00	0,00
Recycled cardboard	3,60	86,47	3,60	100,00
Total incl. packaging	10,50		4,66	

Technical data:

Product version:

K12H - 4-legged, plywood shell

K22H - 4-legged, plywood shell, seat upholstered pad

K32H - 4-legged, plywood shell, seat and backrest, upholstered pads

K42H - 4-legged, fully upholstered

Frame:

H - 4-legged (H) – metal frame, fi 16 mm

2P - version with armrests (plastic or plywood pad)

Table top:

Com H 2P and V 2P may occur with table top (2PB). Folded table top (always black composite (HPL)), assembled on the right side, equipped with anti-panic system which prevents blocking the table top in case of sudden movement.

Stacking:

12H (+2P) - 15 pcs 12H 2PB - 5 pcs

Market:

Worldwide

Reference service life, product

5 years

Reference service life, building

LCA: Calculation rules

Declared unit:



1 pcs Profim Com H

Cut-off criteria:

All major raw materials and all the essential energy is included. The production processes for raw materials and energy flows with very small amounts (less than 1%) are not included. These cut-off criteria do not apply for hazardous materials and substances.

Allocation:

The allocation is made in accordance with the provisions of EN 15804. Incoming energy and water and waste production in-house is allocated equally among all products through mass allocation. Effects of primary production of recycled materials is allocated to the main product in which the material was used. The recycling process and transportation of the material is allocated to this analysis.

Data quality:


Specific data for the product composition are provided by the manufacturer. They represent the production of the declared product and were collected for EPD development in the year of study. Background data is based on registered EPDs according to EN 15804, Ostfold Research databases, ecoinvent and other LCA databases. The data quality of the raw materials in A1 is presented in the table below.

Materials	Source	Data quality	Year
Adhesive	Modified ecoinvent 3.6	Database/Supplier	2019
Metal - Steel	ecoinvent 3.6	Database	2019
Metal - Steel	Modified ecoinvent 3.6	Database	2019
Packaging - Cardboard	Modified ecoinvent 3.6	Database	2019
Packaging - Paper	ecoinvent 3.6	Database	2019
Packaging - Plastic	ecoinvent 3.6	Database	2019
Packaging - Plastic straps	ecoinvent 3.6	Database	2019
Plastic - Polyoxymethylene (POM)	ecoinvent 3.6	Database	2019
Plastic - Polypropylene (PP)	ecoinvent 3.6	Database	2019
Plastic - Polyurethane (PUR)	ecoinvent 3.6	Database	2019
Powder coating	Ecoinvent 3.6	Database	2019
Printed paper	ecoinvent 3.6	Database	2019
Recycled cardboard	Modified ecoinvent 3.6	Database	2019
Textile - Polyester (PE)	ecoinvent 3.6	Database	2019
Textile - Polyester (PE)	Modified ecoinvent 3.6	Database	2019
Wood - Solid beech/birch	modified ecoinvent 3.6	Database	2019

System boundaries (X=included, MND=module not declared, MNR=module not relevant)

Р	roduct stag	ge		uction on stage				Use stage					End of I	Beyond the system boundaries		
Raw materials	Transport	Manufacturing	Transport	Assembly	Use	Maintenance	Repair	Replacement	Refurbishment	Operational energy use	Operational water use	De- construction demolition	Transport	Waste processing	Disposal	Reuse-Recovery- Recycling-potential
A1	A2	A3	A4	A5	B1	B2	В3	B4	B5	В6	В7	C1	C2	C3	C4	D
Χ	Χ	Χ	Χ	Χ	MND	X	Χ	Χ	MND	MND	MND	Χ	X	X	Χ	X

System boundary:



Additional technical information:



LCA: Scenarios and additional technical information

The following information describe the scenarios in the different modules of the EPD.

Transport from production place to user (A4)	Capacity utilisation (incl. return) %	Distance (km)	Fuel/Energy Consumption	Unit	Value (Liter/tonne)
Truck, over 32 tonnes, EURO 5 (km)	53,3 %	1000	0,023	l/tkm	23,00
Assembly (A5)	Unit	Value			
Waste, packaging, cardboard, 100 % recycled, to	kg	3,60			
average treatment (kg) Waste, packaging, corrugated board box, 0 %	kg	0,43			
recycled, to average treatment (kg) Waste, packaging, paper printed, to average					
treatment (kg) Waste, packaging, PET straps, to average	kg	0,02			
treatment - A5 (kg)	kg	0,01			
Waste, packaging, plastic film (LDPE), to average treatment - A5 (kg)	kg	0,10			
Maintenance (B2)	Unit	Value			
Electricity, European average (kWh)	kWh/DU	10,53			
Electricity, World average (kWh)	kWh/DU	1,17			
Water, tap water (m3)	m3/DU	0,78			
Repair (B3)	Unit	Value			
Electricity, European average (kWh)	kWh/DU	0,50			
Electricity, World average (kWh)	kWh/DU	0,06			
Transport to waste processing (C2)	Capacity utilisation	Distance (km)	Fuel/Energy Consumption	Unit	Value
	(incl. return) %				(Liter/tonne)
Truck, 16-32 tonnes, EURO 5 (km)	36,7 %	85	0,044	l/tkm	3,74
Waste processing (C3)	Unit	Value			
Waste treatment per kg Graphical paper, incineration with fly ash extraction (kg)	kg	0,00			
Waste treatment per kg Hazardous waste, incineration (kg)	kg	0,04			
Waste treatment per kg Non-hazardous waste, incineration with fly ash extraction - C3 (kg)	kg	0,03			
Waste treatment per kg Polyoxymethylene (POM), incineration with fly ash extraction (kg) - CH - C3	kg	0,01			
Waste treatment per kg Polypropylene (PP), incineration with fly ash extraction - C3 (kg)	kg	0,30			
Waste treatment per kg Polyurethane (PU), incineration (kg)	kg	0,20			
Waste treatment per kg Scrap steel, incineration with fly ash extraction (kg)	kg	2,39			
Waste treatment per kg Textile, incineration with fly ash extraction (kg)	kg	0,73			
Waste treatment per kg Wood, incineration with fly ash extraction (kg)	kg	2,65			
Waste, materials to recycling (kg)	kg	0,81			
Disposal (C4)	Unit	Value			
Landfilling of ashes and residues from incineration of Scrap steel (kg)	kg	1,58			
Landfilling of ashes from incineration of Graphical paper, process of ashes and residues (kg)	kg	0,00			
Landfilling of ashes from incineration of Hazardous waste, from incineration (kg)	kg	0,01			
Landfilling of ashes from incineration of Non- hazardous waste, process per kg ashes and residues - C4 (kg)	kg	0,01			
Landfilling of ashes from incineration of Polyoxymethylene (POM), process per kg ashes and residues (kg) - CH - C4	kg	0,00			
Landfilling of ashes from incineration of Polypropylene, PP, process per kg ashes and residues - C4 (kg)	kg	0,01			
Landfilling of ashes from incineration of Polyurethane (PU), process per kg ashes and residues - C4 (kg)	kg	0,01			
Landfilling of ashes from incineration of Textile, soiled, process per kg ashes and residues (kg)	kg	0,04			
Landfilling of ashes from incineration of Wood, process per kg ashes and residues (kg)	kg	0,03			



Benefits and loads beyond the system boundaries (D)	Unit	Value		
Substitution of electricity, in Norway (MJ)	MJ	3,30		
Substitution of primary steel with net scrap (kg)	kg	0,66		
Substitution of thermal energy, district heating, in Norway (MJ)	МЈ	49,85		



LCA: Results

The LCA results are presented below for the declared unit defined on page 2 of the EPD document.

Environme	ntal impact								
	Indicator		Unit		A1-A3	A4	A5	B2	В3
	GWP-total	kg CO ₂ -eq		ed	5,12E+00	9,55E-01	6,96E+00	5,67E+00	2,54E-01
	GWP-fossil	kg CO ₂ -eq		eq	1,59E+01	9,55E-01	7,41E-02	5,62E+00	2,52E-01
	GWP-biogenic		kg CO ₂ -e	eq	-1,08E+01	3,92E-04	6,88E+00	3,61E-02	1,62E-03
	GWP-luluc		kg CO ₂ -e	eq	4,35E-02	2,79E-04	2,23E-05	1,27E-02	5,74E-04
٨	ODP		kg CFC11	-eq	1,46E-06	2,21E-07	1,44E-08	4,39E-07	1,95E-08
Œ	АР		mol H+ -	eq	8,59E-02	4,01E-03	3,21E-04	3,22E-02	1,44E-03
	EP-FreshWater		kg P -ed	1	9,41E-04	7,28E-06	5,56E-07	5,47E-04	2,47E-05
	EP-Marine		kg N -ed	7	2,13E-02	1,21E-03	1,12E-04	4,31E-03	1,91E-04
	EP-Terrestial		mol N -e	eq	2,20E-01	1,33E-02	1,15E-03	5,22E-02	2,32E-03
	POCP		kg NMVOC	-eq	7,12E-02	4,29E-03	3,32E-04	1,35E-02	5,94E-04
	ADP-minerals&metals ¹		kg Sb-ed	7	6,26E-04	1,63E-05	1,64E-06	4,34E-05	1,69E-06
	ADP-fossil ¹		MJ		2,33E+02	1,48E+01	9,53E-01	1,08E+02	4,87E+00
<u>%</u>	WDP ¹		m^3		1,31E+04	1,14E+01	1,29E+00	1,51E+03	6,70E+01
	Indicator		Unit	B4	C1	C2	C3	C4	D
	GWP-total		kg CO ₂ -eq	0	0	1,49E-01	6,93E+00	2,28E-02	-1,02E+00
	GWP-fossil		kg CO ₂ -eq	0	0	1,49E-01	1,53E+00	2,28E-02	-1,01E+00
	GWP-biogenic		kg CO ₂ -eq	0	0	6,07E-05	5,40E+00	2,00E-05	-9,95E-04
	GWP-Iuluc		kg CO ₂ -eq	0	0	5,20E-05	3,70E-05	5,95E-06	-1,03E-02
٨	ODP	ı	kg CFC11 -eq	0	0	3,39E-08	1,84E-08	5,84E-09	-2,11E-02
CE CE	АР		mol H+ -eq	0	0	6,08E-04	1,31E-03	1,38E-04	-5,97E-03
	EP-FreshWater		kg P -eq	0	0	1,17E-06	3,45E-06	2,33E-07	-7,01E-05
	EP-Marine		kg N -eq	0	0	1,80E-04	6,23E-04	4,84E-05	-1,52E-03
	EP-Terrestial		mol N -eq	0	0	2,00E-03	6,37E-03	5,38E-04	-1,60E-02
	POCP	k	g NMVOC -eq	0	0	6,11E-04	1,57E-03	1,54E-04	-5,94E-03
	ADP-minerals&metals ¹	kg Sb-eq		0	0	4,03E-06	6,92E-07	3,23E-07	-1,53E-05
	ADP-fossil ¹		MJ	0	0	2,24E+00	1,09E+00	4,38E-01	-1,02E+01
<u>%</u>	WDP ¹		m ³	0	0	2,14E+00	2,63E+00	1,36E+00	-1,40E+01

GWP-total = Global Warming Potential total; GWP-fossil = Global Warming Potential fossil fuels; GWP-biogenic = Global Warming Potential biogenic; GWP-luluc = Global Warming Potential land use and land use change; ODP = Depletion potential of the stratospheric ozone layer; AP = Acidification potential, Accumulated Exceedance; EP-freshwater = Eutrophication potential, fraction of nutrients reaching freshwater end compartment: EP-marine = Eutrophication potential, fraction of nutrients reaching marine end compartment; EP-terrestrial = Eutrophication potential, Accumulated Exceedance; POCP = Formation potential of tropospheric ozone; ADP-minerals&metals = Abiotic depletion potential for non-fossil resources; ADP-fossil = Abiotic depletion for fossil resources potential; WDP = Water (user) deprivation potential, deprivation-weighted water consumption

Remarks to environmental impacts

[&]quot;Reading example: 9,0 E-03 = 9,0*10-3 = 0,009"

^{*}INA Indicator Not Assessed

^{1.} The results of this environmental impact indicator shall be used with care as the uncertainties on these results are high or as there is limited experienced with the indicator



Additional e	nvironmental impa	ct indicators						
	Indicator	Unit	Unit			A5	B2	В3
	PM	Disease incidence	Disease incidence		8,40E-08	4,77E-09	1,14E-07	4,75E-09
	IRP ²	kgBq U235 -eq		6,50E-01	6,49E-02	4,08E-03	8,90E-01	4,03E-02
	ETP-fw ¹	CTUe		1,02E+03	1,09E+01	1,26E+00	8,66E+01	3,84E+00
26. <u>*</u>	HTP-c ¹	CTUh		6,18E-08	0,00E+00	3,70E-11	2,79E-09	9,70E-11
46 B	HTP-nc ¹	CTUh		4,65E-07	1,05E-08	1,57E-09	8,81E-08	3,37E-09
	SQP ¹	dimensionless		3,14E+02	1,70E+01	6,77E-01	2,53E+01	1,13E+00
I	ndicator	Unit	B4	C1	C2	C3	C4	D
	PM	Disease incidence	0	0	1,07E-08	1,36E-08	2,42E-09	-2,04E-07
	IRP ²	kgBq U235 -eq	0	0	9,81E-03	3,12E-03	1,79E-03	-2,38E-02
6	ETP-fw ¹	CTUe	0	0	1,65E+00	5,10E+00	3,14E-01	-6,27E+01
40.4 *** <u>*</u>	HTP-c ¹	CTUh	0	0	0,00E+00	3,73E-10	1,00E-11	-3,88E-09
8° <u>B</u>	HTP-nc ¹	CTUh	0	0	1,79E-09	9,15E-09	3,70E-10	5,39E-08
&	SOP ¹	dimensionless	0	0	1,55E+00	2,56E-01	9,76E-01	-2,81E+01

PM = Particulate Matter emissions; IRP = Ionizing radiation – human health; ETP-fw = Eco toxicity – freshwater; HTP-c = Human toxicity – cancer effects; HTP-nc = Human toxicity – non cancer effects; SQP = Soil Quality (dimensionless)

[&]quot;Reading example: 9,0 E-03 = 9,0*10-3 = 0,009"

^{*}INA Indicator Not Assessed

^{1.} The results of this environmental impact indicator shall be used with care as the uncertainties on these results are high or as there is limited experienced with the indicator

^{2.} This impact category deals mainly with the eventual impact of low dose ionizing radiation on human health of the nuclear fuel cycle. It does not consider effects due to possible nuclear accidents, occupational exposure nor due to radioactive waste disposal in underground facilities. Potential ionizing radiation from the soil, from radon and from some construction materials is also not measured by this indicator.

Flol: l:

Resource use									
	Indicator		U	nit	A1-A3	A4	A5	B2	В3
	PERE		N	N۱	1,45E+02	1,87E-01	1,60E-02	1,99E+01	9,05E-01
	PERM		N	ΜJ	6,54E+01	0,00E+00	-2,83E+01	0,00E+00	0,00E+00
Ę,	PERT		N	ΝJ	2,10E+02	1,87E-01	-2,83E+01	1,99E+01	9,05E-01
3	PENRE		N	MJ	1,95E+02	1,48E+01	9,53E-01	1,08E+02	4,88E+00
Å	PENRM		N	MJ	3,80E+01	0,00E+00	-4,45E+00	0,00E+00	0,00E+00
IA	PENRT		N	MJ	2,33E+02	1,48E+01	-3,49E+00	1,08E+02	4,88E+00
	SM		k	кg	4,66E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00
	RSF		N	WJ	4,48E-01	6,54E-03	5,24E-04	1,38E+00	6,27E-02
	NRSF		N	MJ	1,21E-01	2,19E-02	2,13E-03	3,70E-01	1,51E-02
%	FW			n ³	1,95E-01	1,69E-03	4,51E-04	8,69E-01	3,99E-03
			n	ทั	1,55L-01	1,032 03	1,312 01	0,032 01	3,332 03
Indi	icator	U	Init	B4	C1	C2	C3	C4	D
Indi ুুুু	icator PERE								
		N	Init	B4	C1	C2	C3	C4	D
Č.	PERE	1	Init MJ	B4 0	C1 0	C2 3,17E-02	C3 9,22E-02	C4 1,04E-02	D -2,60E+01
G L	PERE PERM	N N	Init MJ	0 0	C1 0	C2 3,17E-02 0,00E+00	C3 9,22E-02 -3,71E+01	C4 1,04E-02 0,00E+00	D -2,60E+01 0,00E+00
्र 3 ्र	PERE PERM PERT	N N	MJ MJ	0 0 0	C1 0 0	C2 3,17E-02 0,00E+00 3,17E-02	C3 9,22E-02 -3,71E+01 -3,70E+01	C4 1,04E-02 0,00E+00 1,04E-02	D -2,60E+01 0,00E+00 -2,60E+01
. 	PERE PERM PERT PENRE	7 7 7	MI MI MI	B4 0 0 0 0	C1 0 0 0	C2 3,17E-02 0,00E+00 3,17E-02 2,24E+00	C3 9,22E-02 -3,71E+01 -3,70E+01 1,11E+00	C4 1,04E-02 0,00E+00 1,04E-02 4,38E-01	D -2,60E+01 0,00E+00 -2,60E+01 -1,02E+01
E E F	PERE PERM PERT PENRE PENRM	10 10 10 10 10 10 10 10 10 10 10 10 10 1	MJ MJ MJ MJ	B4 0 0 0 0 0	C1 0 0 0 0	C2 3,17E-02 0,00E+00 3,17E-02 2,24E+00 0,00E+00	C3 9,22E-02 -3,71E+01 -3,70E+01 1,11E+00 -3,35E+01	C4 1,04E-02 0,00E+00 1,04E-02 4,38E-01 0,00E+00	D -2,60E+01 0,00E+00 -2,60E+01 -1,02E+01 0,00E+00
	PERE PERM PERT PENRE PENRM PENRT	N N N N N N N N N N N N N N N N N N N	MJ MJ MJ MJ MJ MJ	B4 0 0 0 0 0 0	C1 0 0 0 0 0	C2 3,17E-02 0,00E+00 3,17E-02 2,24E+00 0,00E+00 2,24E+00	C3 9,22E-02 -3,71E+01 -3,70E+01 1,11E+00 -3,35E+01 -3,24E+01	C4 1,04E-02 0,00E+00 1,04E-02 4,38E-01 0,00E+00 4,38E-01	D -2,60E+01 0,00E+00 -2,60E+01 -1,02E+01 0,00E+00 -1,02E+01
	PERE PERM PERT PENRE PENRM PENRT SM	h	MJ MJ MJ MJ MJ MJ kg	B4 0 0 0 0 0 0 0	C1 0 0 0 0 0 0	C2 3,17E-02 0,00E+00 3,17E-02 2,24E+00 0,00E+00 2,24E+00 0,00E+00	C3 9,22E-02 -3,71E+01 -3,70E+01 1,11E+00 -3,35E+01 -3,24E+01 0,00E+00	C4 1,04E-02 0,00E+00 1,04E-02 4,38E-01 0,00E+00 4,38E-01 0,00E+00	D -2,60E+01 0,00E+00 -2,60E+01 -1,02E+01 0,00E+00 -1,02E+01 0,00E+00

PERE = Use of renewable primary energy excluding renewable primary energy resources used as raw materials; PERM = Use of renewable primary energy resources used as raw materials; PERT = Total use of renewable primary energy resources; PENRE = Use of non renewable primary energy resources used as raw materials; PENRM = Use of non renewable primary energy resources used as raw materials; PENRT = Total use of non renewable primary energy resources; SM = Use of secondary materials; RSF = Use of renewable secondary fuels; NRSF = Use of non-renewable secondary fuels; FW = Net use of fresh water

"Reading example: 9,0 E-03 = 9,0*10-3 = 0,009" *INA Indicator Not Assessed

Flol: l:

End of life - Waste									
	Indicator		Unit		A1-A3	A4	A5	B2	В3
	HWD		k	g	2,22E-01	8,13E-04	0,00E+00	1,87E-02	8,39E-04
Ō	NHWD		k	9	4,52E+00	1,29E+00	4,16E+00	4,24E-01	1,73E-02
**	RWD		k	g	6,39E-04	1,01E-04	0,00E+00	7,21E-04	3,26E-05
In	dicator	ı	Unit	B4	C1	C2	C3	C4	D
	HWD		kg	0	0	1,14E-04	0,00E+00	1,61E+00	-3,95E-03
Ī	NHWD		kg	0	0	1,07E-01	7,00E-02	3,67E-02	-3,93E-01
-	RWD		kg	0	0	1,53E-05	0,00E+00	2,59E-06	-1,96E-05

HWD = Hazardous waste disposed; NHWD = Non-hazardous waste disposed; RWD = Radioactive waste disposed

"Reading example: 9,0 E-03 = 9,0*10-3 = 0,009" *INA Indicator Not Assessed

End of life - Output flow								
Ind	icator	Un	Unit		A4	A5	B2	В3
®	CRU	kg	kg		0,00E+00	0,00E+00	0,00E+00	0,00E+00
&▷	MFR	kç	kg		0,00E+00	3,83E+00	0,00E+00	0,00E+00
DF	MER	kç	J	6,61E-06	0,00E+00	1,69E-03	0,00E+00	0,00E+00
50	EEE	М	J	4,60E-01	0,00E+00	2,32E-01	0,00E+00	0,00E+00
DB.	EET	М	J	6,97E+00	0,00E+00	3,51E+00	0,00E+00	0,00E+00
Indicato	or	Unit	B4	C1	C2	C3	C4	D
∅>	CRU	kg	0	0	0,00E+00	0,00E+00	0,00E+00	0,00E+00
\$>	MFR	kg	0	0	0,00E+00	8,10E-01	0,00E+00	0,00E+00
D7	MER	kg	0	0	0,00E+00	6,34E+00	0,00E+00	0,00E+00
50	EEE	МЈ	0	0	0,00E+00	3,19E+00	0,00E+00	0,00E+00
D	EET	MJ	0	0	0,00E+00	4,83E+01	0,00E+00	0,00E+00

CRU = Components for re-use; MFR = Materials for recycling; MER = Materials for energy recovery; EEE = Exported energy electrical; EET = Exported energy thermal

"Reading example: 9,0 E-03 = 9,0*10-3 = 0,009" *INA Indicator Not Assessed

Biogenic Carbon Content								
Indicator	Unit	At the factory gate						
Biogenic carbon content in product	kg C	1,18E+00						
Biogenic carbon content in accompanying packaging	kg C	1,88E+00						

Note: 1 kg biogenic carbon is equivalent to 44/12 kg CO2



Additional requirements

Greenhouse gas emissions from the use of electricity in the manufacturing phase

National production mix from import, low voltage (production of transmission lines, in addition to direct emissions and losses in grid) of applied electricity for the manufacturing process (A3).

Electricity mix	Data source	Amount	Unit
Electricity, high voltage, hydro (kWh) - PL	ecoinvent 3.6	4.02	g CO2-eg/kWh

Dangerous substances

The product contains no substances given by the REACH Candidate list.

Indoor environment

Möbelfakta

Additional Environmental Information

Key Environmental Indicators

Key environmental indicators	Unit	A1-A3	A4	A1-C4	A1-D
GWPtotal	kg CO ₂ -eq	5,12	0,96	26,06	25,04
Total energy consumption	MJ	340,85	15,06	496,62	459,66
Amount of recycled materials	%	44,31			

Additional environmental impact indicators required in NPCR Part A for construction products							
Indicator	Unit	Unit		A4	A5	B2	В3
GWPIOBC	kg CO ₂ -eq	kg CO ₂ -eq		9,55E-01	7,41E-02	5,99E+00	2,69E-01
Indicator	Unit	B4	C1	C2	C3	C4	D
GWPIOBC	kg CO ₂ -eq	0	0	1,49E-01	2,68E+00	2,52E-02	-1,38E+00

GWP-IOBC: Global warming potential calculated according to the principle of instantaneous oxidation. In order to increase the transparency of biogenic carbon contribution to climate impact, the indicator GWP-IOBC is required as it declares climate impacts calculated according to the principle of instantaneous oxidation. GWP-IOBC is also referred to as GWP-GHG in context to Swedish public procurement legislation.

Variants and Options

Key environmental indicators (A1-A3) for variants of this EPD							
Variants	Weight (kg)	GWPtotal (kg CO ₂ - eq)	Total energy consumption (MJ)	Amount of recycled materials (%)			
Profim Com K12H Natural Wood shell, w/o armrests - No Packaging	5,40	6,29	197,08	8,48			
Profim Com K12H HPL Wood shell, w/o armrests - No Packaging	5,45	7,68	210,25	8,41			
Profim Com K22H Natural Wood shell, w/o armrests - No Packaging	6,64	7,10	238,55	11,12			
Profim Com K22H HPL Wood shell, w/o armrests - No Packaging	6,69	8,48	251,72	11,05			
Profim Com K32H Natural Wood shell, w/o armrests - No Packaging	7,74	8,06	274,83	13,21			
Profim Com K32H HPL Wood shell, w/o armrests - No Packaging	7,76	9,39	287,29	13,17			
Profim Com K42H Full Uph shell (Xtreme/Camira), w/o armrests - No Packaging	6,37	7,74	223,82	16,62			
Profim Com H Trolley - No Packaging	13,81	49,89	706,40	18,29			

Key environmental indicators (A1-A3) for options for this EPD						
Options	Weight (kg)	GWPtotal (kg CO ₂ - eq)	Total energy consumption (MJ)	Amount of recycled materials (%)		
Profim Com H - Armrests with Plastic pads	1,61	4,00	49,60	19,14		
Profim Com H - Armrests with Natural Wood pads	1,67	3,61	48,65	18,48		
Profim Com H - Armrests with HPL Wood pads	1,69	3,68	49,84	18,26		
Profim Com H - Writing table	1,97	2,99	65,34	0,12		
Profim Com H/V - Linking system	0,31	1,08	12,25	0,00		
Profim Com H - System "anti-panic" (APA)	0,51	1,34	17,10	0,00		
Profim Com H - System "anti-panic" (APB)	0,74	1,91	23,80	0,00		
Profim Com H - System "anti-panic" (APD)	0,57	1,46	17,28	0,00		
Profim Com H - Packaging no. 1 (1-5 chair/s in foil bag, no carton box)	0,16	0,29	7,14	29,26		
Profim Com H - Packaging no. 2 (1-2 chair/s in 1 box)	4,16	-2,61	117,19	86,67		
Profim Com H - Packaging no. 3 (3-5 chairs in 1 box)	1,11	-0,41	31,69	71,60		
Profim Com Trolley - Packaging	3,75	-2,18	104,31	96,17		



Bibliography

ISO 14025:2010 Environmental labels and declarations - Type III environmental declarations - Principles and procedures.

ISO 14044:2006 Environmental management - Life cycle assessment - Requirements and guidelines.

EN 15804:2012 + A2:2019 Environmental product declaration - Core rules for the product category of construction products.

ISO 21930:2017 Sustainability in buildings and civil engineering works - Core rules for environmental product declarations of construction products.

ecoinvent v3, Allocation, cut-off by classification, Swiss Centre of Life Cycle Inventories.

Iversen et al., (2021) eEPD v2021.09 Background information for EPD generator tool system verification, LCA.no Report number: 07.21 Ruud et al., (2023) EPD generator for NPCR026 Part B for Furniture - Background information for EPD generator application and LCA data, LCA.no report number 01.23

NPCR Part A: Construction products and services. Ver. 2.0. March 2021, EPD-Norge.

NPCR 026 Part B for Furniture. Ver. 2.0 March 2022, EPD-Norge.

© epd-norway		Program operator and publisher	Phone:	+47 23 08 80 00
		The Norwegian EPD Foundation	e-mail:	post@epd-norge.no
	Global Program Operator	Post Box 5250 Majorstuen, 0303 Oslo, Norway	web:	www.epd-norge.no
		Owner of the declaration:	Phone:	0047 98 25 68 30
li lol:l:		Flokk AS	e-mail:	atle.messel@flokk.com
	1 1 0 10 10	Drammensveien 145,, 0277 Oslo	web:	https://www.flokk.com
		Author of the Life Cycle Assessment	Phone:	+47 916 50 916
	(LCA)	LCA.no AS	e-mail:	post@lca.no
	.no	Dokka 6B, 1671	web:	www.lca.no
		Developer of EPD generator	Phone:	+47 916 50 916
	(LCA)	LCA.no AS	e-mail:	post@lca.no
	.no	Dokka 6B,1671 Kråkerøy	web:	www.lca.no
	EGO PLATFORM	ECO Platform	web:	www.eco-platform.org
	VERIFIED	ECO Portal	web:	ECO Portal