



Product Service

CERTIFICATE

No. Z1A 090658 0092 Rev. 00

Certificate Holder: Flokk Sp.z o.o.
Górnicza 8
62-700 Turek
POLAND

Approval mark:



Product: Office chairs

Tested according to: DIN EN 1335-1:2020
DIN EN 1335-2:2019
AfPS GS 2019:01 PAK

GS TÜV SÜD Product Service GmbH, the notified body, acting within the scope of its power in accordance with § 20 ProdSG (German Law on the Provision of Products on the Market), by issue of this Certificate, has approved the specified certificate holder to mark the indicated product of the given model designation with the GS-conformity mark. The product meets the requirements of § 20 sec.3 of the Product Safety Act (ProdSG) in terms of safety and health protection. The manufacturer's obligations specified in § 24 ProdSG shall be adhered to. The certified product may be marked with approval marks shown above. Test rating presentation may not be changed. This certificate is non-transferable to Third Parties and remains valid until the given date unless it has been prematurely cancelled. All applicable requirements set out in the test and certification regulation of TÜV SÜD Gruppe shall be met. For details - visit: www.tuvsud.com/ps-zert

Report no: 713268966

Valid until: 21 November 2027

Date, 22 November 2022

(Jens Biesenack)

CERTIFICATE

No. Z1A 090658 0092 Rev. 00

Model(s): **My Turn S (My Turn Synchro)**

Characteristics:

| | |
|-------------------|---|
| Seat support | <p>The seat is height adjustable and equipped with a synchronous mechanism for the inclination of the seat surface</p> <p>Seat height: 415 – 515 mm</p> <p>Seat depth: 500 mm</p> |
| Height adjustment | <p>Seat height adjustment by means of gas pressure spring.</p> <p>Manufacturer: Samhongs Co., Ltd., Tube model: SG, Material: STKM 12, Wall thickness: 2,5 mm, Surface: Heat treatment, class 4 according to EN16955:2017</p> |
| Seat surface | <p>Seat frame of aluminium, upholstered, covered with leather or textile</p> |
| Backrest | <p>Frame of the backrest in aluminium, upholstered, covered with leather or textile. The backrest is fixed in depth and height. Height of the backrest above the seat: 810 mm.</p> |
| Armrests | <p>Plastic armrests. The armrests and armrest cushions are firm in every direction.</p> <p>Armrest length: 246 mm</p> <p>Armrest width: 93 mm</p> <p>Distance between the armrests: 530 mm</p> |
| Underframe | <p>Aluminium underframe</p> <p>Maximum offset of the underframe: 406 mm</p> |
| Castors | <p>Load-dependent braked double castors Ø 65 mm, type "H" for soft floors or type "W" for hard floors.</p> |
| Chair type | <p>C (according to DIN EN 1335-1:2020)</p> |