

# Environmental product declaration

in accordance with ISO 14025 and EN 15804+A2

## Profim Revo Tables



**profim**

---

**Flokk**

EPD-Global

**Owner of the declaration:**

Flokk AS

**Product:**

Profim Revo Tables

**Declared unit:**

1 pcs

**This declaration is based on Product Category Rules:**

CEN Standard EN 15804:2012+A2:2019 serves as core PCR  
NPCR 026:2022 Part B for Furniture

**Program operator:**

EPD-Global

**Declaration number:**

NEPD-15118-17792

**Issue date:**

09.03.2026

**Valid to:**

09.03.2031

**EPD software:**

LCAno EPD generator ID: 1458143

## General information

### Product

Profim Revo Tables

### Program operator:

EPD-Global  
Post Box 5250 Majorstuen, 0303 Oslo, Norway  
Phone: +47 977 22 020  
web: [www.epd-global.com](http://www.epd-global.com)

### Declaration number:

NEPD-15118-17792

### This declaration is based on Product Category Rules:

CEN Standard EN 15804:2012+A2:2019 serves as core PCR  
NPCR 026:2022 Part B for Furniture

### Statement of liability:

The owner of the declaration shall be liable for the underlying information and evidence. EPD-Global shall not be liable with respect to manufacturer information, life cycle assessment data and evidences.

### Declared unit:

1 pcs Profim Revo Tables

### Declared unit (cradle to gate) with option:

A1-A3, A4, A5, B2, B3, B4, C1, C2, C3, C4, D

### Functional unit:

1 pcs Profim Revo T75 — Table (Top + Metal Frame), 750 × 750 × 740 mm, Square Flat Base — Including packaging.

### General information on verification of EPD from EPD tools:

Independent verification of data, other environmental information and the declaration according to ISO 14025:2010, § 8.1.3 and § 8.1.4. Verification of each EPD is made according to EPD-Global's guidelines for verification and approval requiring that tools are i) integrated into the company's environmental management system, ii) the procedures for use of the EPD tool are approved by EPD-Global, and iii) the process is reviewed annually by an independent third party verifier. See Appendix G of EPD-Global's General Programme Instructions for further information on EPD tools

### Verification of EPD tool:

Independent third party verification of the EPD tool, background data and test-EPD in accordance with EPD-Global's procedures and guidelines for verification and approval of EPD tools.

Third party verifier:

Elisabet Amat, GREENIZE projects

(no signature required)

### Owner of the declaration:

Flokk AS  
Contact person: Atle Thiis-Messel  
Phone: 0047 98 25 68 30  
e-mail: [atle.messel@flokk.com](mailto:atle.messel@flokk.com)

### Manufacturer:

Flokk AS  
Drammensveien 145,  
0277 Oslo, Norway

### Place of production:

Flokk - Turek  
ul. Górnicza 8  
62-700 Turek, Poland

### Management system:

ISO 14001, ISO 9001.

### Organisation no:

No 928 902 749

### Issue date:

09.03.2026

### Valid to:

09.03.2031

### Year of study:

2025

### Comparability:

EPD of construction products may not be comparable if they not comply with EN 15804 and seen in a building context.

### Development and verification of EPD:

The declaration is created using EPD tool lca.tools ver EPD2022.03, developed by LCA.no. The EPD tool is integrated in the company's management system, and has been approved by EPD-Global.

Developer of EPD: Damian Bakowski

Reviewer of company-specific input data and EPD: Damian Piterek

### Approved:



Håkon Hauan, CEO EPD-Global

## Product

### Product description:

Revo collection of tables was designed by the famous London-based design studio Pearson Lloyd. The collection includes three types of tables in various sizes: conference tables, coffee tables and small auxiliary tables that can be matched with sofas or armchairs.

### Product specification

The model analyzed in detail in this declaration is the Profim Revo T75 — Table (Top + Metal Frame), 750 × 750 × 740 mm, Square Flat Base, including packaging. Key environmental indicators for other models and options of the Profim Revo Tables are presented in a table on page 12 of this declaration.

Materials	kg	%	Recycled share in material (kg)	Recycled share in material (%)
Chemical	0.075	0.3831	0.00	0.00
Glue for wood	0.085	0.4342	0.00	0.00
Metal - Steel	13.87	70.84	2.74	19.78
Powder coating	0.172	0.8787	0.00	0.00
Textile - Felt	0.004	0.02043	0.00	0.00
Wood - Plywood	4.61	23.56	0.00	0.00
Wood - Solid ash	0.76	3.88	0.00	0.00
Total	19.58	100.00	2.74	

Packaging	kg	%	Recycled share in material (kg)	Recycled share in material (%)
Packaging - Paper	0.028	0.9422	0.009607	0.009607
Packaging - Plastic	0.1399	4.71	0.00	0.00
Packaging - Plastic straps	0.0192	0.6461	0.00	0.00
Recycled cardboard	2.78	93.70	2.78	2.78
Total incl. packaging	22.55	100.00	5.54	

### Technical data:

The Revo collection comprises indoor tables available in 8 product versions with varying dimensions, heights and base geometries (square, rectangular or round flat base). The range includes conference tables, coffee tables and auxiliary tables intended for office and public interior applications.

The product consists of a powder-coated steel frame with a flat base and a replaceable table top. Available table top finishes include natural veneer, coloured natural veneer (ash base), and high-pressure laminate (HPL).

The metal frame is also available separately for assembly with table tops made of plywood or solid wood. Assembly with glass table tops is not recommended.

### Market:

Worldwide.

A4 stage transportation from factory to market, is assumed to be 1.000 km.

### Reference service life, product

15 years (warranty 5 years)

### Reference service life, building

N/A

## LCA: Calculation rules

### Declared unit:

1 pcs Profim Revo Tables

### Cut-off criteria:

All major raw materials and all the essential energy is included. The production processes for raw materials and energy flows with very small amounts (less than 1%) are not included. These cut-off criteria do not apply for hazardous materials and substances.

### Allocation:

The allocation is made in accordance with the provisions of EN 15804. Incoming energy and water and waste production in-house is allocated equally among all products through mass allocation. Effects of primary production of recycled materials is allocated to the main product in which the material was used. The recycling process and transportation of the material is allocated to this analysis.

### Data quality:


Specific data for the product composition are provided by the manufacturer. They represent the production of the declared product and were collected for EPD development in the year of study. Background data is based on registered EPDs according to EN 15804, Ostfold Research databases, ecoinvent and other LCA databases. The data quality of the raw materials in A1 is presented in the table below.

Materials	Source	Data quality	Year
Chemical	ecoinvent 3.6	Database	2019
Glue for wood	ecoinvent 3.6	Database	2019
Metal - Steel	ecoinvent 3.6	Database	2019
Metal - Steel	Modified ecoinvent 3.6	Database	2019
Packaging - Paper	ecoinvent 3.6	Database	2019
Packaging - Plastic	ecoinvent 3.6	Database	2019
Packaging - Plastic straps	ecoinvent 3.6	Database	2019
Powder coating	ecoinvent 3.6	Database	2019
Recycled cardboard	Modified ecoinvent 3.6	Database	2019
Textile - Felt	Modified ecoinvent 3.6	Database	2019
Wood - Plywood	modified ecoinvent 3.6	Database	2019
Wood - Solid ash	modified ecoinvent 3.6	Database	2019

### System boundaries (X=included, MND=module not declared, MNR=module not relevant)

Product stage			Construction installation stage		Use stage						End of life stage				Beyond the system boundaries	
Raw materials	Transport	Manufacturing	Transport	Assembly	Use	Maintenance	Repair	Replacement	Refurbishment	Operational energy use	Operational water use	De-construction demolition	Transport	Waste processing	Disposal	Reuse-Recovery-Recycling-potential
A1	A2	A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
X	X	X	X	X	MND	X	X	X	MND	MND	MND	X	X	X	X	X

### System boundary:



### Additional technical information:

## LCA: Scenarios and additional technical information

The following information describe the scenarios in the different modules of the EPD.

Transport from production place to user (A4)	Capacity utilisation (incl. return) %	Distance (km)	Fuel/Energy Consumption	Unit	Value (Liter/tonne)
Truck, over 32 tonnes, EURO 5 (km)	53.3 %	1000.00	0.023	l/tkm	23.00
Assembly (A5)					
	Unit	Value			
Waste, packaging, paper printed, to average treatment (kg)	kg	0.02813			
Waste, packaging, plastic film (LDPE), to average treatment - A5 (kg)	kg	0.1737			
Waste, packaging, PET straps, to average treatment - A5 (kg)	kg	0.0192			
Waste, packaging, plastic tape, to average treatment (kg)	kg	0.00625			
Waste, packaging, cardboard, 100 % recycled, to average treatment (kg)	kg	2.81			
Waste, packaging, corrugated board box, 0 % recycled, to average treatment (kg)	kg	0.02201			
Maintenance (B2)					
	Unit	Value			
Electricity, European average (kWh)	kWh	10.53			
Water, tap water (m3)	m3	0.78			
Electricity, World average (kWh)	kWh	1.17			
Repair (B3)					
	Unit	Value			
Electricity, European average (kWh)	kWh	0.495			
Electricity, World average (kWh)	kWh	0.055			
Transport to waste processing (C2)					
	Capacity utilisation (incl. return) %	Distance (km)	Fuel/Energy Consumption	Unit	Value (Liter/tonne)
Truck, 16-32 tonnes, EURO 5 (km)	36.7 %	85.00	0.044	l/tkm	3.74
Waste processing (C3)					
	Unit	Value			
Waste treatment per kg Textile, incineration with fly ash extraction (kg)	kg	0.004			
Waste treatment per kg Wood, incineration with fly ash extraction (kg)	kg	5.37			
Waste treatment per kg Non-hazardous waste, incineration with fly ash extraction - C3 (kg)	kg	0.172			
Waste, materials to recycling (kg)	kg	4.71			
Waste treatment per kg Scrap steel, incineration with fly ash extraction (kg)	kg	13.87			
Waste treatment per kg Hazardous waste, incineration (kg)	kg	0.16			
Disposal (C4)					
	Unit	Value			
Landfilling of ashes from incineration of Textile, soiled, process per kg ashes and residues (kg)	kg	0.0002009			
Landfilling of ashes from incineration of Wood, process per kg ashes and residues (kg)	kg	0.06179			
Landfilling of ashes from incineration of Non-hazardous waste, process per kg ashes and residues - C4 (kg)	kg	0.04081			
Landfilling of ashes and residues from incineration of Scrap steel (kg)	kg	9.16			
Landfilling of ashes from incineration of Hazardous waste, from incineration (kg)	kg	0.03024			
Benefits and loads beyond the system boundaries (D)					
	Unit	Value			
Substitution of primary steel with net scrap (kg)	kg	3.77			
Substitution of electricity, in Norway (MJ)	MJ	3.84			
Substitution of thermal energy, district heating, in Norway (MJ)	MJ	58.12			

## LCA: Results

The LCA results are presented below for the declared unit defined on page 2 of the EPD document.

Environmental impact							
Indicator	Unit	A1-A3	A4	A5	B2	B3	
GWP-total	kg CO <sub>2</sub> -eq	2.73E+01	2.05E+00	4.92E+00	5.67E+00	2.54E-01	
GWP-fossil	kg CO <sub>2</sub> -eq	4.04E+01	2.05E+00	6.21E-02	5.62E+00	2.52E-01	
GWP-biogenic	kg CO <sub>2</sub> -eq	-1.32E+01	8.41E-04	4.86E+00	3.61E-02	1.62E-03	
GWP-luluc	kg CO <sub>2</sub> -eq	7.69E-02	5.98E-04	1.65E-05	1.27E-02	5.74E-04	
ODP	kg CFC11 -eq	2.86E-06	4.73E-07	1.07E-08	4.39E-07	1.95E-08	
AP	mol H+ -eq	2.27E-01	8.61E-03	2.39E-04	3.22E-02	1.44E-03	
EP-FreshWater	kg P -eq	2.56E-03	1.56E-05	4.13E-07	5.47E-04	2.47E-05	
EP-Marine	kg N -eq	4.62E-02	2.59E-03	9.03E-05	4.31E-03	1.91E-04	
EP-Terrestrial	mol N -eq	5.22E-01	2.86E-02	8.55E-04	5.22E-02	2.32E-03	
POCP	kg NMVOC -eq	1.91E-01	9.21E-03	2.49E-04	1.35E-02	5.94E-04	
ADP-minerals&metals <sup>1</sup>	kg Sb-eq	8.09E-04	3.50E-05	1.21E-06	4.34E-05	1.69E-06	
ADP-fossil <sup>1</sup>	MJ	4.89E+02	3.19E+01	7.13E-01	1.08E+02	4.87E+00	
WDP <sup>1</sup>	m <sup>3</sup>	1.39E+04	2.45E+01	1.05E+00	1.51E+03	6.70E+01	

Indicator	Unit	B4	C1	C2	C3	C4	D
GWP-total	kg CO <sub>2</sub> -eq	0	0	3.20E-01	9.85E+00	1.14E-01	-4.50E+00
GWP-fossil	kg CO <sub>2</sub> -eq	0	0	3.19E-01	8.88E-01	1.14E-01	-4.49E+00
GWP-biogenic	kg CO <sub>2</sub> -eq	0	0	1.30E-04	8.96E+00	8.14E-05	-2.98E-03
GWP-luluc	kg CO <sub>2</sub> -eq	0	0	1.12E-04	1.25E-04	3.21E-05	-1.35E-02
ODP	kg CFC11 -eq	0	0	7.28E-08	5.50E-08	3.24E-08	-2.45E-02
AP	mol H+ -eq	0	0	1.31E-03	1.90E-03	7.49E-04	-2.34E-02
EP-FreshWater	kg P -eq	0	0	2.51E-06	1.21E-05	1.13E-06	-2.85E-04
EP-Marine	kg N -eq	0	0	3.87E-04	7.11E-04	2.65E-04	-5.18E-03
EP-Terrestrial	mol N -eq	0	0	4.28E-03	7.66E-03	2.94E-03	-5.34E-02
POCP	kg NMVOC -eq	0	0	1.31E-03	2.04E-03	8.44E-04	-2.35E-02
ADP-minerals&metals <sup>1</sup>	kg Sb-eq	0	0	8.65E-06	2.05E-06	1.80E-06	-7.50E-05
ADP-fossil <sup>1</sup>	MJ	0	0	4.82E+00	2.75E+00	2.41E+00	-3.97E+01
WDP <sup>1</sup>	m <sup>3</sup>	0	0	4.60E+00	7.96E+00	6.02E+00	1.55E+02

GWP-total = Global Warming Potential total; GWP-fossil = Global Warming Potential fossil fuels; GWP-biogenic = Global Warming Potential biogenic; GWP-luluc = Global Warming Potential land use and land use change; ODP = Depletion potential of the stratospheric ozone layer; AP = Acidification potential, Accumulated Exceedance; EP-freshwater = Eutrophication potential, fraction of nutrients reaching freshwater end compartment; EP-marine = Eutrophication potential, fraction of nutrients reaching marine end compartment; EP-terrestrial = Eutrophication potential, Accumulated Exceedance; POCP = Formation potential of tropospheric ozone; ADP-minerals&metals = Abiotic depletion potential for non-fossil resources; ADP-fossil = Abiotic depletion for fossil resources potential; WDP = Water (user) deprivation potential, deprivation-weighted water consumption

"Reading example: 9.0 E-03 = 9.0\*10<sup>-3</sup> = 0.009"

1. The results of this environmental impact indicator shall be used with care as the uncertainties on these results are high or as there is limited experienced with the indicator

### Remarks to environmental impacts

Additional environmental impact indicators							
Indicator	Unit	A1-A3	A4	A5	B2	B3	
PM	Disease incidence	4.40E-06	1.80E-07	3.58E-09	1.14E-07	4.75E-09	
IRP <sup>2</sup>	kgBq U235 -eq	1.49E+00	1.39E-01	3.07E-03	8.90E-01	4.03E-02	
ETP-fw <sup>1</sup>	CTUe	2.06E+03	2.33E+01	9.26E-01	8.66E+01	3.84E+00	
HTP-c <sup>1</sup>	CTUh	2.76E-07	0.00E+00	2.70E-11	2.79E-09	9.70E-11	
HTP-nc <sup>1</sup>	CTUh	1.99E-06	2.25E-08	1.15E-09	8.81E-08	3.37E-09	
SQP <sup>1</sup>	dimensionless	1.26E+03	3.66E+01	5.48E-01	2.53E+01	1.13E+00	

Indicator	Unit	B4	C1	C2	C3	C4	D
PM	Disease incidence	0	0	2.30E-08	4.11E-08	1.34E-08	-5.13E-07
IRP <sup>2</sup>	kgBq U235 -eq	0	0	2.11E-02	1.00E-02	9.71E-03	-1.59E-02
ETP-fw <sup>1</sup>	CTUe	0	0	3.55E+00	1.46E+01	1.54E+00	-2.58E+02
HTP-c <sup>1</sup>	CTUh	0	0	0.00E+00	1.21E-09	5.60E-11	-2.04E-08
HTP-nc <sup>1</sup>	CTUh	0	0	3.83E-09	1.53E-08	1.61E-09	4.09E-07
SQP <sup>1</sup>	dimensionless	0	0	3.32E+00	8.45E-01	5.26E+00	-3.48E+01

PM = Particulate Matter emissions; IRP = Ionizing radiation – human health; ETP-fw = Eco toxicity – freshwater; HTP-c = Human toxicity – cancer effects; HTP-nc = Human toxicity – non cancer effects; SQP = Soil Quality (dimensionless)

"Reading example: 9.0 E-03 = 9.0\*10<sup>-3</sup> = 0.009"

1. The results of this environmental impact indicator shall be used with care as the uncertainties on these results are high or as there is limited experienced with the indicator
2. This impact category deals mainly with the eventual impact of low dose ionizing radiation on human health of the nuclear fuel cycle. It does not consider effects due to possible nuclear accidents, occupational exposure nor due to radioactive waste disposal in underground facilities. Potential ionizing radiation from the soil, from radon and from some construction materials is also not measured by this indicator.

Resource use								
Indicator		Unit	A1-A3	A4	A5	B2	B3	
	PERE	MJ	3.11E+02	4.01E-01	1.23E-02	1.99E+01	9.05E-01	
	PERM	MJ	9.18E+01	0.00E+00	-1.72E+01	0.00E+00	0.00E+00	
	PERT	MJ	4.03E+02	4.01E-01	-1.72E+01	1.99E+01	9.05E-01	
	PENRE	MJ	4.83E+02	3.19E+01	7.13E-01	1.08E+02	4.88E+00	
	PENRM	MJ	7.20E+00	0.00E+00	-8.04E+00	0.00E+00	0.00E+00	
	PENRT	MJ	4.90E+02	3.19E+01	-7.33E+00	1.08E+02	4.88E+00	
	SM	kg	5.54E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	
	RSF	MJ	7.61E-01	1.40E-02	3.97E-04	1.38E+00	6.27E-02	
	NRSF	MJ	2.49E-01	4.70E-02	1.57E-03	3.70E-01	1.51E-02	
	FW	m <sup>3</sup>	4.33E-01	3.63E-03	3.40E-04	8.69E-01	3.99E-03	

Indicator		Unit	B4	C1	C2	C3	C4	D
	PERE	MJ	0	0	6.80E-02	3.26E-01	5.02E-02	-3.26E+01
	PERM	MJ	0	0	0.00E+00	-7.52E+01	0.00E+00	0.00E+00
	PERT	MJ	0	0	6.80E-02	-7.48E+01	5.02E-02	-3.26E+01
	PENRE	MJ	0	0	4.82E+00	2.76E+00	2.41E+00	-3.97E+01
	PENRM	MJ	0	0	0.00E+00	-2.02E+02	0.00E+00	0.00E+00
	PENRT	MJ	0	0	4.82E+00	-2.00E+02	2.41E+00	-3.97E+01
	SM	kg	0	0	0.00E+00	0.00E+00	0.00E+00	0.00E+00
	RSF	MJ	0	0	2.43E-03	7.13E-03	1.27E-03	1.45E-01
	NRSF	MJ	0	0	8.69E-03	0.00E+00	7.25E-02	2.60E+00
	FW	m <sup>3</sup>	0	0	5.07E-04	3.28E-03	2.22E-03	-4.46E-02

PERE = Use of renewable primary energy excluding renewable primary energy resources used as raw materials; PERM = Use of renewable primary energy resources used as raw materials; PERT = Total use of renewable primary energy resources; PENRE = Use of non renewable primary energy excluding non-renewable primary energy resources used as raw materials; PENRM = Use of non renewable primary energy resources used as raw materials; PENRT = Total use of non renewable primary energy resources; SM = Use of secondary materials; RSF = Use of renewable secondary fuels; NRSF = Use of non-renewable secondary fuels; FW = Net use of fresh water

"Reading example: 9.0 E-03 = 9.0\*10<sup>-3</sup> = 0.009"

End of life - Waste							
Indicator		Unit	A1-A3	A4	A5	B2	B3
	HWD	kg	3.52E-01	1.74E-03	0.00E+00	1.87E-02	8.39E-04
	NHWD	kg	1.44E+01	2.77E+00	3.06E+00	4.24E-01	1.73E-02
	RWD	kg	1.46E-03	2.18E-04	0.00E+00	7.21E-04	3.26E-05

Indicator		Unit	B4	C1	C2	C3	C4	D
	HWD	kg	0	0	2.46E-04	0.00E+00	9.19E+00	-2.18E-02
	NHWD	kg	0	0	2.30E-01	3.32E-01	1.04E-01	-1.81E+00
	RWD	kg	0	0	3.28E-05	0.00E+00	1.44E-05	-1.38E-05

HWD = Hazardous waste disposed; NHWD = Non-hazardous waste disposed; RWD = Radioactive waste disposed

"Reading example: 9.0 E-03 = 9.0\*10<sup>-3</sup> = 0.009"

End of life - Output flow							
Indicator		Unit	A1-A3	A4	A5	B2	B3
	CRU	kg	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
	MFR	kg	8.27E-01	0.00E+00	2.76E+00	0.00E+00	0.00E+00
	MER	kg	6.98E-01	0.00E+00	1.98E-03	0.00E+00	0.00E+00
	EEE	MJ	4.60E-01	0.00E+00	1.64E-01	0.00E+00	0.00E+00
	EET	MJ	6.97E+00	0.00E+00	2.48E+00	0.00E+00	0.00E+00

Indicator		Unit	B4	C1	C2	C3	C4	D
	CRU	kg	0	0	0.00E+00	0.00E+00	0.00E+00	0.00E+00
	MFR	kg	0	0	0.00E+00	4.71E+00	0.00E+00	0.00E+00
	MER	kg	0	0	0.00E+00	1.96E+01	0.00E+00	0.00E+00
	EEE	MJ	0	0	0.00E+00	4.12E+00	0.00E+00	0.00E+00
	EET	MJ	0	0	0.00E+00	6.24E+01	0.00E+00	0.00E+00

CRU = Components for re-use; MFR = Materials for recycling; MER = Materials for energy recovery; EEE = Exported energy electrical; EET = Exported energy thermal

"Reading example: 9.0 E-03 = 9.0\*10<sup>-3</sup> = 0.009"

Biogenic Carbon Content		
Indicator	Unit	At the factory gate
Biogenic carbon content in product	kg C	2.44E+00
Biogenic carbon content in accompanying packaging	kg C	1.30E+00

Note: 1 kg biogenic carbon is equivalent to 44/12 kg CO<sub>2</sub>

## Additional requirements

### Greenhouse gas emissions from the use of electricity in the manufacturing phase

National production mix from import, low voltage (production of transmission lines, in addition to direct emissions and losses in grid) of applied electricity for the manufacturing process (A3).

Electricity mix	Source	Amount	Unit
Electricity, high voltage, hydro (kWh) - PL	ecoinvent 3.6	4.02	g CO <sub>2</sub> -eq/kWh

### Dangerous substances

The product contains no substances given by the REACH Candidate list.

### Indoor environment

Greenguard Gold.

## Additional Environmental Information

### Key Environmental Indicators

Key environmental performance indicators	Unit	Product stage	Construction stage		Use stage			End-of-life				Net benefits and loads from reuse, recovery, and/or recycling
		A1-A3	A4	A5	B2	B3	B4	C1	C2	C3	C4	D
GWP <sub>total</sub>	kg CO <sub>2</sub> -eq	27.28	2.05	4.92	5.67	0.25	0.00	0.00	0.32	9.85	0.11	-4.50
Total energy consumption	MJ	794.55	32.34	0.73	129.93	5.86	0.00	0.00	4.90	3.10	2.53	-69.58
Share of recycled materials	%	24.54										

### Additional environmental impact indicators required in NPCR Part A for construction products

Indicator	Unit	A1-A3	A4	A5	B2	B3
GWPIOBC	kg CO <sub>2</sub> -eq	4.10E+01	2.05E+00	6.21E-02	5.66E+00	2.53E-01

Indicator	Unit	B4	C1	C2	C3	C4	D
GWPIOBC	kg CO <sub>2</sub> -eq	0	0	3.20E-01	8.97E-01	1.15E-01	-4.50E+00

GWP-IOBC: Global warming potential calculated according to the principle of instantaneous oxidation. In order to increase the transparency of biogenic carbon contribution to climate impact, the indicator GWP-IOBC is required as it declares climate impacts calculated according to the principle of instantaneous oxidation. GWP-IOBC is also referred to as GWP-GHG in context to Swedish public procurement legislation.

### Variants and Options

**Key environmental indicators (A1-A3) for variants of this EPD**

Variants	Weight (kg)	GWPTotal (kg CO <sub>2</sub> -eq)	Total energy consumption (MJ)	Amount of recycled materials (%)
Profim Revo T75 — Table (Top + Metal Frame), 750 x 750 x 740 mm, Square Flat Base — No Packaging	19.58	28.79	709.83	14.01
Profim Revo T150 — Table (Top + Metal Frame), 1500 x 700 x 740 mm, Rectangular Flat Base — No Packaging	39.82	58.60	1418.12	14.08
Profim Revo T180 — Table (Top + Metal Frame), 1800 x 850 x 740 mm, Rectangular Flat Base — No Packaging	49.54	68.57	1783.27	13.55
Profim Revo LS65 — Table (Top + Metal Frame), 650 x 350 x 665 mm, Rectangular Flat Base — No Packaging	6.17	7.41	256.87	27.35
Profim Revo LR48 — Table (Top + Metal Frame), Round 480 mm, Height 665 mm, Round Flat Base — No Packaging	8.78	17.47	312.49	16.70
Profim Revo C75 — Table (Top + Metal Frame), 750 x 750 x 450 mm, Square Flat Base — No Packaging	18.72	26.72	683.42	13.77
Profim Revo C150 — Table (Top + Metal Frame), 1500 x 750 x 450 mm, Rectangular Flat Base — No Packaging	38.12	54.47	1365.53	13.84
Profim Revo MT140 — Table (Top + Metal Frame), 1400 x 700 x 650 mm, Rectangular Flat Base — No Packaging	34.61	51.38	1242.75	13.51
Profim Revo T75 — Metal Frame Only, Height 730 mm, Square Flat Base — No Packaging	14.03	34.32	451.70	19.54
Profim Revo T150 — Metal Frame Only, Height 740 mm, Rectangular Flat Base — No Packaging	28.91	71.04	924.91	19.39
Profim Revo T180 — Metal Frame Only, Height 740 mm, Rectangular Flat Base — No Packaging	34.53	84.40	1091.70	19.45
Profim Revo LS65 — Metal Frame Only, Height 660 mm, Rectangular Flat Base — No Packaging	8.64	21.39	289.32	19.54
Profim Revo LR48 — Metal Frame Only, Height 660 mm, Round Flat Base — No Packaging	7.50	18.70	255.81	19.53
Profim Revo C75 — Metal Frame Only, Height 450 mm, Square Flat Base — No Packaging	13.18	32.24	425.17	19.56
Profim Revo C150 — Metal Frame Only, Height 440 mm, Rectangular Flat Base — No Packaging	26.46	64.13	829.12	19.54
Profim Revo MT140 — Metal Frame Only, Height 640 mm, Rectangular Flat Base — No Packaging	28.44	69.85	893.87	16.43

**Key environmental indicators (A1-A3) for options for this EPD**

Options	Weight (kg)	GWPTotal (kg CO <sub>2</sub> -eq)	Total energy consumption (MJ)	Amount of recycled materials (%)
Profim Revo T75 — Complete Unit (Top + Metal Frame) — Packaging	2.97	-1.51	84.72	94.03
Profim Revo T150 — Complete Unit (Top + Metal Frame) — Packaging	8.42	-3.59	227.44	57.63
Profim Revo T180 — Complete Unit (Top + Metal Frame) — Packaging	11.78	-6.36	303.91	51.33
Profim Revo LS65 — Complete Unit (Top + Metal Frame) — Packaging	2.08	-1.12	59.22	94.85
Profim Revo LR48 — Complete Unit (Top + Metal Frame) — Packaging	2.08	-1.12	59.22	94.85
Profim Revo C75 — Complete Unit (Top + Metal Frame) — Packaging	2.97	-1.52	84.66	94.07
Profim Revo C150 — Complete Unit (Top + Metal Frame) — Packaging	8.29	-3.50	223.88	57.00
Profim Revo MT140 — Complete Unit (Top + Metal Frame) — Packaging	8.42	-3.59	227.44	57.63
Profim Revo T75 — Metal Frame Only — Packaging	2.09	-1.09	59.71	94.45
Profim Revo T150 — Metal Frame Only — Packaging	2.51	-0.44	76.60	85.24
Profim Revo T180 — Metal Frame Only — Packaging	2.51	-0.44	76.60	85.24
Profim Revo LS65 — Metal Frame Only — Packaging	2.08	-1.12	59.22	94.85
Profim Revo LR48 — Metal Frame Only — Packaging	2.08	-1.12	59.22	94.85
Profim Revo C75 — Metal Frame Only — Packaging	2.08	-1.12	59.16	94.90
Profim Revo C150 — Metal Frame Only — Packaging	5.75	-1.45	158.14	38.01
Profim Revo MT140 — Metal Frame Only — Packaging	2.51	-0.44	76.60	85.24

## Bibliography

ISO 14025:2010 Environmental labels and declarations - Type III environmental declarations - Principles and procedures.  
 ISO 14044:2006 Environmental management - Life cycle assessment - Requirements and guidelines.  
 EN 15804:2012+A2:2019 Environmental product declaration - Core rules for the product category of construction products.  
 ISO 21930:2017 Sustainability in buildings and civil engineering works - Core rules for environmental product declarations of construction products.  
 ecoinvent v3, Allocation, cut-off by classification, Swiss Centre of Life Cycle Inventories.  
 Iversen et al., (2021) eEPD v2021.09 Background information for EPD generator tool system verification, LCA.no Report number: 07.21  
 Ruud et al., (2023) EPD generator for NPCR026 Part B for Furniture - Background information for EPD generator application and LCA data, LCA.no report number 01.23  
 NPCR Part A: Construction products and services. Ver. 2.0. March 2021, EPD-Norge.  
 NPCR 026 Part B for Furniture. Ver. 2.0 March 2022, EPD-Norge.

 <small>Powered by EPD-Norway</small>	<b>Program operator and publisher</b> EPD-Global Postboks 5250 Majorstuen, 0303 Oslo, Norway	Phone: +47 977 22 020 e-mail: post@epd-norge.no web: www.epd-global.com
	<b>Owner of the declaration:</b> Flokk AS Drammensveien 145,, 0277 Oslo, Norway	Phone: 0047 98 25 68 30 e-mail: atle.messel@flokk.com web: https://www.flokk.com
	<b>Author of the Life Cycle Assessment</b> LCA.no AS Dokka 6A, 1671 Kråkerøy, Norway	Phone: +47 916 50 916 e-mail: post@lca.no web: www.lca.no
	<b>Developer of EPD generator</b> LCA.no AS Dokka 6A, 1671 Kråkerøy, Norway	Phone: +47 916 50 916 e-mail: post@lca.no web: www.lca.no
	ECO Platform ECO Portal	web: www.eco-platform.org web: ECO Portal